



**DANISH MARITIME AUTHORITY**

**SØFARTSSTYRELSEN  
DANISH MARITIME AUTHORITY  
TYPEGODKENDELSESCERTIFIKAT  
Type approval certificate**

**DET BEKRÆFTES HERMED AT KONSTRUKTIONEN AF:**

**This is to certify that the design of:**

Dykkertelefon inklusiv telefonlivline, type JHT "2005", "2005DS", "2005video" and "2005DS video".

Telephone system for use at diving including safety line, type JHT "2005", "2005DS", "2005video" and "2005DS video".

**PRODUKT BESKRIVELSE:**

**Product description:**

Se tillæg 1.

See Appendix 1

**FABRIKANT:**

**Manufacturer:**

JH-Teknik

Webergade 44

2100 Copenhagen Ø

Denmark

**ER I OVERENSSTEMMELSE MED :**

**Is found to comply with:**

Bekendtgørelse nr. 823 af 5. november 1999 om dykkermateriel §§ 5 og 6.

Order no. 823 of 5 November 1999 on Diving equipment §§ 5 and 6.

**ANVENDELSE:**

**Application:**

Samtaleanlæg for 2 dykkere og overfladen ved dykning med atmosfærisk luft indtil 50 meters dybde.

Intercommunication system for 2 divers and the surface at diving with atmospheric air on depth less than 50 metres.

**GODKENDELSESKRITERIER:**

**Approval conditions:**

Se tillæg 1.

See appendix

**DENNE TYPEGODKENDELSE ER GYLDIG INDTIL:**

**This type approval is valid until:**

**31 March 2010**

**UDSTEDT I KØBENHAVN**

**Issued at Copenhagen**

14 March 2006

File 200601892



Niels Nielsen



**DANISH MARITIME AUTHORITY**

**SØFARTSSTYRELSEN  
DANISH MARITIME AUTHORITY**

**TILLÆG 1 TIL TYPEGODKENDELSESCERTIFIKAT  
Appendix 1 to type approval certificate**

**GODKENDELSESKRITERIER:**

**Approval conditions:**

Udstyret består af duplex dykkertelefon for 2 dykkere og én tender samt båndoptager og ext. højttaler, udført i slagfast plast med tænd/sluk funktion, telefonlivline, stik samt oplader.

Instruktions- og vedligeholdelsesbog skal medleveres udstyret.

Maksimum dykkerdybde 50 meter.

Længde af telefonlivline minimum 5 meter længere end dykkerdybden, dog mindst 20 meter lang.

Udstyret skal mærkes med fabrikat og/eller type, serienummer og fremstillingsår.

En kopi af dette certifikat skal medfølge hver telefon.

The equipment consist of a duplex telephone system for 2 divers, tape recoder, external loudspeaker and for one diving assistant, made of shockproof plastic with on/off function, safety line (telephone wire) and charger.

Instruction- and maintenance book must be delivered with each system.

Maksimum diving depth is 50 metres.

The length of the safety line (telephone wire) must be minimum 5 meters longer than the diving depth, and minimum 20 metres.

The equipment must be marked with manufacturer and/or type, serial number and year of production.

A copy of this certificate must follow each telephone.

Enhver ændring i forhold til den godkendte prototype, herunder ændringer i det for godkendelsen nødvendige tegningsmateriale, ændringer i godkendt produktionskontrol eller ændringer i forhold til øvrige godkendelsesvilkår, hvortil Søfartsstyrelsens skriftlige tilladelse ikke foreligger, medfører automatisk, at typegodkendelsen bortfalder.

Any conversion of the product compared to the approved prototype, including modifications of approved drawings, approved production control, or other conditions of approval, for which no written permission is given from the Danish Maritime Authority, shall automatically result in withdrawal of the type approval.

Uanset Søfartsstyrelsens godkendelsesbetingelser påhviler produktansvaret leverandøren.

Regardless of the Danish Maritime Authority's type approval conditions, the liability for the product rests with the supplier.

**UDSTEDT I KØBENHAVN**

Issued at Copenhagen

on

14 March 2006

File 200601892

Tillæg slut

End of appendix



Niels Nielsen